


品赞电子(东莞)有限公司

品赞电子(东莞)有限公司



G-Switch USB-C Specification:

- 1.Current rated: 5A on vbus/1.25A on vconn/0.25A on other
- Voltage rating: 24V AC
- 2.Withstanding voltage: 100V AC/minute
- 3.Contact resistance: 40mΩ Max
- 4.Insulation resistance: 100MΩ Min
- 5.Operating temperature: -40°C ~ +85°C
- 6.Mating force: 5N~20N
- 7.Unmating force: 8N~20N
- 8.Durability cycle:10,000 cycles
- 9.Compliant with: IEC62680-1-3

A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
GND			VBUS	CC1	D+	D-	SBU1	VBUS			GND
First			First	Second	Second	Second	Second	First			First

B12	B11	B10	B9	B8	B7	B6	B5	B4	B3	B2	B1
GND			VBUS	SBU2	D-	D+	CC2	VBUS			GND
First			First	Second	Second	Second	Second	First			First

USB IF TID:12233

SCALE: 1:1 UNIT: mm

SIZE: A4

Title: Horizontal Type-c 16P Female
SMT Pad up3.27 CH=4.8 L=8.0mm

Molde Code: GT-USB-9016F01

DRAWN	CHECKED	APPROVED	DATE
Xla	Chen	Chen	2023,02,01

REV: A0 SHEET: 1/1

b-Switch
www.dg-switch.com