







SECTION A-A


USB IF
TID:11807**G-Switch USB-C Specification:**

- 1.Current rated: 5A on vbus/1.25A on vconn/0.25A on other
- 2.Withstanding voltage: 100V AC/minute
- 3.Contact resistance: 40mΩ Max
- 4.Insulation resistance: 100MΩ Min
- 5.Operating temperature: -40°C ~ +85°C
- 6.Mating force: 5N~20N
- 7.Unmating force: 8N~20N
- 8.Durability cycle:10,000 cycles
- 9.Waterproof grade: IP-X7.
- 10.Compliant with:IEC62680-1-3

A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
GND			VBUS	CC1	D+	D-	SBU1	VBUS			GND
First			First	Second	Second	Second	Second	First			First

B12	B11	B10	B9	B8	B7	B6	B5	B4	B3	B2	B1
GND			VBUS	SBU2	D-	D+	CC2	VBUS			GND
First			First	Second	Second	Second	Second	First			First

NO.	PARTS	MATERIAL	REMARKS
1	COVER SHELL	HIGH TEMPERATURE PLASTIC	PA BLACK
2	SHELL	STAINLESS STEEL	Ni30u"Min PLATED
3	MID PLATE	STAINLESS STEEL	CLEAN
4	HOUSING	HIGH TEMPERATURE PLASTIC	PA BLACK UL 94 V-0
5	TERMINALS	COPPER ALLOY	Au1u"Min PLATING ON CONTACT AREA
6	RUBBER	SILICA GEL	BLACK

**RoHS**
Compliant
EU RoHS StandardsSCALE: 1:1 UNIT: mm
SIZE: A4Unless otherwise
General Tolerance:
X.x ±0.30
X.xx ±0.20
X.xxx ±0.10
X.x" ±3°
X.xx" ±2°Title: Vertical Type-c 16P Female
DIP H=11.3mm

Molde Code: GT-USB-9069D

DRAWN	CHECKED	APPROVED	DATE
Xia	Chen	Chen	2023.02.01

b-Switch
www.dg-switch.com

REV: A0 SHEET: 1/2