

1

2

品赞电子（东莞）有限公司

4

5

A

B

G-Switch Technology (Dongguan) Co., Ltd

D

E

1








2

品赞电子（东莞）有限公司

4

5

E



G-Switch USB-C Specification:

- 1.Current rated: 5A on vbus/1.25A on vconn/0.25A on other
- Voltage rating: 24V AC
- 2.Withstanding voltage: 100V AC/minute
- 3.Contact resistance: 40mΩ Max
- 4.Insulation resistance: 100MΩ Min
- 5.Operating temperature: -40°C ~ +85°C
- 6.Mating force : 5N~20N
- 7.Unmating force: 8N~20N
- 8.Durability cycle:10,000 cycles
- 9.Data transmission rate up to 5Gbps
- 10.Compliant with: IEC62680-1-3

USB IF TID:13188

A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
GND	TX1+	TX1-	VBUS	CC1	D+	D-	SBU1	VBUS	RX2-	RX2+	GND
First	Second	Second	First	Second	Second	Second	Second	First	Second	Second	First
B12	B11	B10	B9	B8	B7	B6	B5	B4	B3	B2	B1
GND	RX1+	RX1-	VBUS	SBU2	D-	D+	CC2	VBUS	TX2-	TX2+	GND
First	Second	Second	First	Second	Second	Second	Second	First	Second	Second	First

1	SHELL	STAINLESS STEEL304	Ni30u"MIN PLATED
2	MID PLATE	STAINLESS STEEL301	Ni30u"MIN PLATED
3	HOUSING	HIGH TEMPERATURE PLASTIC	PA9T BLACK UL 94 V-0
4	TERMINALS	COPPER ALLOY C7025	Au1u"MIN PLATING ON CONTACT AREA Au1u"MIN PLATING ON SOLDER AREA
5	EMI	STAINLESS STEEL304	--
NO.	PARTS	MATERIAL	REMARKS

RECOMMENDED P.C.B. LAYOUT
TOLERANCE UNSPECIFIED ±0.05mm



SCALE: 1:1	UNIT: mm	Title: Horizontal Type-c 24P Female SMT CH=1.68 L=7.9mm			
SIZE: A4		Molde Code: GT-USB-9013A			
Unless otherwise General Tolerance: X..x ±0.30 X..xx ±0.20 X..xxx ±0.10 X..x° ±3° X..xx° ±2°		DRAWN	CHECKED	APPROVED	DATE
		Xia	Chen	Chen	2023.02.01



REV: A0	SHEET: 1/1
---------	------------