






G-Switch USB-C Specification:

1. Current rating: 5A on Vbus/1.25A on Vconn/0.25A on other
2. Voltage rating: 24V AC
3. Dielectric Voltage: 100V AC/minute
4. Contact resistance: 40mΩ Max
5. Insulation resistance: 100MΩ Min
6. Operating temperature: -55 °C ~ +85 °C
7. Mating force: 5N~20N
8. Unmating force: 8N~20N
9. Durability cycle: 10,000 cycles
10. Data transmission rate up to 5Gbp/s
10. Compliant with: IEC62680-1-3


USB IF TID:13339



SECTION A-A
AFTER MATING

A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
GND	SSTXp1	SSTXn1	VBUS	CC1	Dp1	Dn1	SBU1	VBUS	SSRXn2	SSRXp2	GND
First	Second	Second	First	Second	Second	Second	Second	First	Second	Second	First
B12	B11	B10	B9	B8	B7	B6	B5	B4	B3	B2	B1
GND	SSRXp1	SSRXn1	VBUS	SBU2	Dn2	Dp2	CC2	VBUS	SSTXn2	SSTXp2	GND
First	Second	Second	First	Second	Second	Second	Second	First	Second	Second	First

1	SHELL	STAINLESS STEEL	Ni30MIN Plated
2	MID PLATE	STAINLESS STEEL	_____
3	EMI	STAINLESS STEEL	_____
4	HOUSING	HIGH TEMPERATURE PLASTIC	LCP Black UL 94 V-0
5	TERMINALS	COPPER ALLOY C7025	Au1u"Min PLATING ON CONTACT AREA
NO.	PARTS	MATERIAL	REMARKS



RoHS
Compliant
EU RoHS Standards



SCALE: 4:1

UNIT: mm

SIZE:

Unless otherwise
General Tolerance:

X.x	±0.30
X.xx	±0.20
X.xxx	±0.10
X.x°	±3°
X.xx°	±2°

Title: Vertical Type-c 24P Female
SMT H=6.5mm

Molde Code: GT-USB-9052A

DRAWN

CHECKE

APPROVED

DATE _____



品贊科技

b-Switch

www.dg-switch.com

REV: A0

A0

SHEET:

1/1