



USB IF TID:12315

A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
GND	TX1+	TX1-	VBUS	CC1	D+	D-	SBU1	VBUS	RX2-	RX2+	GND
First	Second	Second	First	Second	Second	Second	Second	First	Second	Second	First
B12	B11	B10	B9	B8	B7	B6	B5	B4	B3	B2	B1
GND	RX1+	RX1-	VBUS	SBU2	D-	D+	CC2	VBUS	TX2-	TX2+	GND
First	Second	Second	First	Second	Second	Second	Second	First	Second	Second	First

Three RoHS compliance logos are displayed in a row. The first logo on the left is a circle with a diagonal line through it, containing the letters 'Pb', with the text 'Process Capable' below it. The middle logo is a rounded rectangle containing the text 'RoHS Compliant' and 'EU RoHS Standards'. The third logo on the right is a circle with a diagonal line through it, containing the letters 'H', with the text 'Compliant Halogen Free' below it.

SCALE: 1:1	UNIT: mm	Title: Splint0.25/0.8/1.0/1.2 Type-c 24P Female SMT L=9.3mm			
SIZE: A4					
Unless otherwise General Tolerance: X.x ±0.30 X.xx ±0.20 X.xxx ±0.10 X.x° ±3° X.xx° ±2°		Molde Code: GT-USB-9011B			
		DRAWN	CHECKED	APPROVED	DATE
		Jiang	Xia	Chen	2023.02.01

