

GT-TA045X-HXXX-LX A

G-Switch

Operating Force



A=160gf
B=250gf
C=220gf

DETAIL

A=Base With Pilot
N=Non Pilot

Switch Height (mm)
H036=3.60

Switch Lifetime (Force)
L1=100,000 Cycles




RECOMMENDED PCB LAYOUT
TOLERANCE:±0.05

G-Switch Specification:

1. Operating temperature range: -40°C ~ +85°C
2. Rating: 50mA.12V DC
3. Insulation resistance: 100MΩ min.100V DC
4. Dielectric strength: 250V AC for 1 min
5. Contact resistance: 100mΩ max.
6. Travel: 0.25±0.1mm

6	COVER	COPPER ALLOY	Ag PLATING
5	STEM	HIGH TEMPERATURE PLASTIC	BLACK
4	TAPE	POLYIMIDE	YELLOW (TRANSPARENT)
3	CONTACT	STAINLESS STEEL	Ag PLATING
2	TERMINAL	COPPER ALLOY	Ag PLATING
1	BASE	HIGH TEMPERATURE PLASTIC	BLACK
NO.	PART NAME	MATERIAL	REMARK



CIRCUIT DIAGRAM



SCALE: 1:1 UNIT: mm
SIZE: A4

Unless otherwise
General Tolerance:
X. ±0.40
X.x ±0.30
X.xx ±0.20
X* ±3°

Title: Horizontal Tact Switch
U Type CH=0.74 3.5×3.0×Hmm

Molde Code: GT-TA045X-HXXX-LXA

DRAWN	CHECKED	APPROVED	DATE
Jiang	Xia	Chen	2025.02.09



REV: A0 SHEET: 1/1