



GT-TB045X-HXXX-LX N

G-Switch

Operating Force



A=160gf
B=250gf
C=220gf

DETAIL

A=Base With Pilot
N=Non Pilot

Switch Height (mm)
H036=3.60

Switch Lifetime (Force)
L1=100,000 Cycles




RECOMMENDED PCB LAYOUT
TOLERANCE:±0.05

G-Switch Specification:

1. Operating temperature range: -40°C ~ +85°C
2. Rating: 50mA.12V DC
3. Insulation resistance: 100MΩ min.100V DC
4. Dielectric strength: 250V AC for 1 min
5. Contact resistance: 100mΩ max.
6. Travel: 0.20±0.1mm

7	TAPE	PI	-
6	COVER	STAINLESS STEEL	-
5	STEM	HIGH TEMPERATURE PLASTIC	PA
4	TAPE	POLYIMIDE	-
3	CONTACT	STAINLESS STEEL	Ag PLATING
2	TERMINAL	PHOSPHOR BRONZE	Ag PLATING
1	BASE	HIGH TEMPERATURE PLASTIC	BLACK
NO.	PART NAME	MATERIAL	REMARK



CIRCUIT DIAGRAM



SCALE: 1:1	UNIT: mm	Title: Horizontal Tact Switch Flat CH=0.65 3.5×3.0×Hmm			
SIZE: A4		Molde Code: GT-TB045X-HXXX-LXN			
Unless otherwise General Tolerance: X. ±0.40 X.x ±0.30 X.xx ±0.20 X* ±3°		DRAWN	CHECKED	APPROVED	DATE
		Jiang	Xia	Chen	2025.02.12
		REV: A0			
		SHEET: 1/1			

