




GT-B0502 F S V 21 -XX X XX 02

G-Switch
Series No
F-Female
Termipoint
S-SMT
Angle
V-180°
Terminal Plating
11-All Au G/F
Housing Colour
S-Nature
B-Black
Pin Q' PY
10~80
Height
21-2.10mm

G-Switch Specification:
1.Current rated: 0.3A AC/DC
2.Voltage rating: 50V AC/DC
3.Withstanding voltage: 150V AC
4.Contact resistance: 50mΩ Max.
5.Insulation resistance: 500MΩ min
6.Durability cycle: 30Cycles
7.Removal force: 0.30kgf/Pin min
8.Operating temperature range: -40°C ~ +85°C

Ordering Information:

Circuit	Dimensions(mm)				Circuit	Dimensions(mm)			
	A	B	C	D		A	B	C	D
10	4.70	2.00	3.20	4.10	32	10.20	7.50	8.70	9.60
12	5.20	2.50	3.70	4.60	36	11.20	8.50	9.70	10.60
14	5.70	3.00	4.20	5.10	40	12.20	9.50	10.70	11.60
20	7.20	4.50	5.70	6.60	50	14.70	12.00	13.20	14.10
22	7.70	5.00	6.20	7.10	60	17.20	14.50	15.70	16.60
24	8.20	5.50	6.70	7.60	70	19.70	17.00	18.20	19.10
30	9.70	7.00	8.20	9.10	80	22.10	19.50	20.70	21.60

3	SOLDER TABS	PHOSPHOR BRONZE	BRIGHT Tin
2	CONTACT	PHOSPHOR BRONZE	ALL Au G/F
1	HOUSING	LCP,94V-0	NATURE
NO.	PART NAME	MATERIAL	REMARK



SCALE: 1:1	UNIT: mm	Title: BTB 0.50mm Pitch 180° H2.1mm Dual Rows SMT Type Femate Connector			
SIZE: A4					
Unless otherwise General Tolerance: X ±0.40 X.x ±0.30 X.xx ±0.20 X° ±5° X.x° ±3°		Molde Code: GT-B0502FSV21-XXXXX02			
		DRAWN	CHECKED	APPROVED	DATE
		Hu	Chen	Chen	2022.12.28

品赞科技
b-Switch
www.dg-switch.com

REV: A0 SHEET: 1/1